

RIG SPECIFICATION SHEET

Arabdrill 110 (AD110)



| | |
|--------------------------|-----------------------------------|
| Rig HP Rating | 3000 hp |
| Design | KFELS Mod-V Class B |
| Rig Builder /Year | KFELS Yard, Singapore/ 2015 |
| Classification | ABS Class MA A1 |
| Load Rating | 1,500,000 lbs |
| Rated Drilling Depth | 30,000 ft |
| Water Depth | Min 25 ft & max 400 ft |
| Overall Dimensions | 234 ft X 208 ft X 25 ft |
| Transit/jacking/Elevated | 4500 Kips, 17,168 Kips, 7500 Kips |
| Cantilever Envelope | 70 ft long. x 15 ft trans. |
| POB | 130 |

DERRICK

| | |
|--------------------|----------------------------------|
| Make | Lee C Moore (Woolslayer Company) |
| Height | 160 ft |
| Static Hook Load | 1,500,000 lbs |
| Drilling Line Size | 1-5/8" |

TOP DRIVE

| | |
|-------------------|------------------------|
| Make / Model | NOV / TDS-8SA |
| Load Rating | 750 t, 1150 hp GEB20B2 |
| Max. Drill Torque | 62,250 ft-lb |
| Breakout Torque | 95,000 ft-lb |

MUD PUMPS

| | |
|-----------------------|--------------|
| Make/Model | LEWCO/W-2215 |
| Number of pumps | 3 |
| Max. Input Horsepower | 2200 hp |
| Standpipe Pressure | 7,500 psi |

POWER GENERATION

| | |
|-------------------|----------------------|
| Make/ Model | CAT/ 3516 CHD - 5 ea |
| Horsepower Rating | 2150 hp |
| Kilowatt Rating | 1720 kW |

DRAW WORKS

| | |
|-------------------|----------------|
| Make | NOV |
| Model | ADS-10T |
| Input Power | GEB22A2 - 3 ea |
| Horsepower Rating | 3000 hp |

ROTARY / SLIP TABLE

| | |
|--------------------|-------------|
| Make / Model | NOV RST 495 |
| Table Opening Size | 49 1/2" |

MUD SYSTEM

| | |
|------------------------|------------|
| Active (usable) Volume | 4,000 bbls |
| Number of Tanks | 7 |
| Solid Control System | 4 Brandts |

DECK CRANES

| | |
|-----------------|--|
| Make & Capacity | 3 ea. Favelle Favco, Diesel/Hydraulic, CAT C-15 Engine |
|-----------------|--|

TRAVELLING ASSEMBLY

| | |
|------------------|----------------------------------|
| Crown Block | Lee C Moore (Woolslayer Company) |
| Load Rating | 860 t |
| Travelling Block | NOV/DRECO Model 760TB-750-8C |
| Load Rating | 750 t |

WELL CONTROL

| | |
|-----------------------------|--------------------------------------|
| Annular Preventer | NOV Shaffer SBOP |
| Pressure Rating | 5,000 PSI |
| Big Bore Diverter | DrillQuip 500, 49.5" |
| Diversers | NOV Shaffer SBOP : 21.1/4-2M & 30-1M |
| Ram Preventer | Cameron Type "U" Double & Single |
| Choke | MTQ |
| Manifold Pressure Rating | 5,000 psi |
| Size | 3-1/8" |
| Accumulator Pressure Rating | 3000 psi |
| MGS | 48" |

ADDITIONAL EQUIPMENT

| | |
|---------------------|--|
| BOP Handling | 2 x 82.5 Tons each Ingersoll Rand BOP handling hoists |
| Emergency Generator | 1 ea Caterpillar 3508DITA Engine, Stamford PM736 Generator, Output 692kW, 480V |
| Iron Roughneck | NOV AR 3200M (main), NOV ST-120 (offline) |
| OA Crane | 16 K Fourm, 16,000 lb SWL |



* Applies to Mast / Derrick and Substructure.